



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/095011 A1

(51) International Patent Classification⁷: G01N 27/00

(21) International Application Number:

PCT/GB2004/001609

(22) International Filing Date: 14 April 2004 (14.04.2004)

(25) Filing Language: English

(26) **Publication Language:** English

(30) Priority Data:

0308950.5 17 April 2003 (17.04.2003) GB

0321443.4 12 September 2003 (12.09.2003) GB

(71) Applicant (for all designated States except US): AKUBIO LIMITED [GB/GB]; 112 Hills Road, Cambridge CB2 1PH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): OSTANIN, Victor, Petrovich [GB/GB]; 84 Alex Wood Road, Cambridge, Cambridgeshire CB4 2EH (GB).

(74) **Agent: GILL JENNINGS & EVERY:** Broadgate House,
7 Eldon Street, London EC2M 7LH (GB).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR). OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS TO RUPTURE EVENT SENSORS



(57) Abstract: An apparatus for separating an analyte from a mixture or for detecting an analyte or for determining the affinity, or a property related to affinity, between binding partners is described. The apparatus comprises: a) a surface having the analyte or one of the binding partners immobilised thereon, in use; b) a transducer for oscillating the surface; c) a controller connected to the transducer for varying the amplitude and/or frequency of the oscillation to cause a dissociation event; and, d) an analyser connected to the transducer for detecting an oscillation of the transducer due to the dissociation event. The controller includes an oscillator connected in a resonant circuit with the transducer such that the transducer oscillates at two frequencies simultaneously, one of these causing the transducer to oscillate the surface and the other being supplied as an output to the analyser.

WO 2004/095011 A1